

# FOTOGRAFIT

Category **Strobes - Flash**

## Sea and Sea YS-D2

Product no.: 03117

**688,75 EUR (incl. VAT)**

Powerful and reliable underwater flash  
Sea & Sea.

The YS-D2 sets a new standard for underwater strobes. From subtle light output as low as guide number 1 to a maximum power of guide number 32, control of underwater lighting has become effortless with the YS-D2.

The new Sea & Sea YS-D2 flash replaces the already highly popular YS-D1 model with a number of improvements:

- Faster recharging - With lithium battery, flash is ready again in 1.4 seconds
- Redesigned buttons - You will no longer accidentally get turned on one of the buttons
- Target light with two options (100/300 lumen) and red filter
- The rear panel is with backlit lights, so you can see the buttons in the dark
- Audible sound when the flash is ready again
- Redesigned casing, which protects the rest of the flash in the event of a leak

Specs for Sea & Sea YS-D2: Guide Number (ISO 100) 32

- with diffuser nr. 100: 24
- with diffuser nr. 120: 20

Light angle: 80 x 80

- with diffuser nr. 100: 100 x 100
- with diffuser nr. 120: 120 x 120.

Batteries 4xAA Alkaline: 6V Ni-MH: 4.8V.

The number of flashes: Alkaline: 150  
Ni-MH: 200

Recharge time (full)

Alkaline: 3.0 sec.



Ni-MH: 1.5 sec.

Color temperature:  
Color temperature without diffuser:  
5600K  
Color temperature with diffuser:  
5250K.

Depth rating:  
100m.

Dimensions:  
(WxHxD) 89x133x116mm  
Weight 623g. (without batteries)  
Underwater weight: 0,40 g. with  
batteries

Other specs:  
Exposure control:  
DS-TTL II, Slave TTL

Light level knob (GN):  
1 / 1.4 / 2 / 2.8 / 4 / 5.6 / 8/11/16/22/32  
(11 steps).

Pre-flash control:  
Equipped with pre-flash cancelled  
mode.

DS-TTL mode.  
Slave mode.  
Auto Power Off function.  
Sync cable, fibre optic cable (L-type).  
Pressure relief valve.  
LED target light (100/300 lumen)  
Adjustable audio signal when the flash  
is ready.  
Backlit Panel (aqua blue / blue / green  
/ orange)